

THE BASIC-D and BASIC-S

The most competitively priced Braille embossers in their class



Now With USB and Network Support

- With the Basic embossers, the cost of producing Braille is decreased to a level slightly above a quality laser printer. The user's options combined with the speed and record of reliability make the Basic S and Basic D the most competitively priced embossers available.
- You control the Basic embossers with a front panel labeled both in ink and in Braille, that gives you voice confirmation of the keys pressed, thus making them the most user-friendly line of Braille embossers available.
 - The Basic embossers are able to produce graphics as well as regular Braille text with excellent durability and high speed.
 - The USB, Ethernet, parallel, and serial interfaces insure easy connection to your computer or network.



BASIC D double-sided (interpoint) Braille embosser

The double-sided function reduces the cost of paper by 50%, and reduces the binding and mailing costs as well. 13 hardened hammers striking against 13 hardened steel anvils insure durability and excellent Braille quality at 340 pages per hour (or 100 characters per second).

BASIC-S single-sided Braille embosser

Is similar to Basic-D, but available in a single-sided lower cost version. Embosses at 50 cps or 170 pages per hour.

TECHNICAL SPECIFICATIONS

Speed:	BASIC S - 170 PPH (pages per hour) or 50 cps BASIC D - 340 PPH (pages per hour) or 100 cps
Printing principle:	13 (Basic D) or 6 (Basic S) high quality hardened hammers forming against hardened steel anvils
Text buffer:	512 KB (app. 400 Braille pages)
Paper:	Continuous tractor feed paper.
Graphics:	Resolution 2.5mm 2.0 mm and 1.6 mm
Characters per line:	Interpoint maximum 42 characters per line Interline maximum 48 characters per line
Interface:	USB, Ethernet, Parallel and Serial interface
Approval:	Complies with Part 15 of the FCC and the CE regulation.
Electrical:	Switched power supply 100-240 volt, 50-60 Hz.
Braille tables:	Up to 20 computer or literary tables
Warranty:	One year parts, labor and return shipment from repair facility to customer site
Size:	W x D x H: 20.2" x 10" x 5"
Weight:	16 lbs.